

## CLAIMS

What is claimed is:

1. A method for monitoring for the successful transmission of a sequence of command  
5 codes transmitted from a remote control, the method comprising:  
    receiving a transmission from the remote control comprising at least a part of the  
sequence of command codes;  
    determining if the transmission from the remote control included all of the  
command codes in the sequence of command codes; and  
10      when the transmission from the remote control is determined to include less than  
all of the command codes in the sequence of command codes, performing an action for  
the purpose of initiating a retransmission of at least those command codes in the sequence  
of command codes determined to be missing.
- 15 2. The method as recited in claim 1, wherein the action comprises generating an audible  
signal.
3. The method as recited in claim 1, wherein the action comprises generating a visual  
signal.
- 20 4. The method as recited in claim 1, wherein the action comprises directly retransmitting  
at least those command codes in the sequence of command codes determined to be  
missing.

5. The method as recited in claim 1, wherein the action comprises sending a signal to the remote control to cause the remote control to retransmit at least those command codes in the sequence of command codes determined to be missing.

5

6. The method as recited in claim 5, wherein the signal comprises data indicative of command codes within the sequence of command codes determined to be missing from the sequence of command codes.

10 7. The method as recited in claim 5, wherein the signal comprises command codes within the sequence of command codes determined to be missing from the sequence of command codes.

8. The method as recited in claim 1, wherein the action comprises transmitting a signal to  
15 a secondary device to cause the secondary device to retransmit at least those command codes in the sequence of command codes determined to be missing.

9. A remote control transmission monitoring system, comprising:

a remote control having programming for transmitting a sequence of command  
20 codes; and

a command receiver having programming for determining if the transmission from the remote control included all of the command codes in the sequence of command

codes and for performing an action for the purpose of initiating a retransmission of at least those command codes in the sequence of command codes determined to be missing.

10. The system as recited in claim 9, wherein the action comprises generating an audible  
5 signal.

11. The system as recited in claim 9, wherein the action comprises generating a visual signal.

10 12. The system as recited in claim 9, wherein the action comprises transmitting a signal to the remote control to cause the remote control to retransmit at least those command codes in the sequence of command codes determined to be missing.

13. The system as recited in claim 12, wherein the signal comprises data indicative of  
15 command codes within the sequence of command codes determined to be missing from the sequence of command codes and the remote control has programming for using the data to retransmit the command codes within the sequence of command codes determined to be missing from the sequence of command codes.

20 14. The system as recited in claim 12, wherein the signal comprises command codes within the sequence of command codes determined to be missing from the sequence of command codes and the remote control has programming for retransmitting the command

codes within the sequence of command codes determined to be missing from the sequence of command codes.

15. The system as recited in claim 9, wherein the command receiver is further adapted to  
5 learn the sequence of command codes directly from the remote control.

16. The system as recited in claim 9, wherein the command receiver is further adapted to communicate with a network whereby the sequence of command codes is downloadable into the command receiver.

10

17. The system as recited in claim 9, wherein the command receiver further includes a keypad for use in teaching the sequence of command codes to the command receiver.

18. The system as recited in claim 9, wherein the command receiver is integrated within  
15 a home appliance.

19. The system as recited in claim 9, wherein the command receiver is adapted to prevent the performance of operations of a home appliance corresponding to the sequence of command codes until such time as it is determined that all of the command codes  
20 within the sequence have been successfully received by the command receiver.

20. The system as recited in claim 9, wherein the command receiver is adapted to cause an appliance to perform all of the operations corresponding to the sequence of command

codes when it is determined that the command receiver has received less than all of the command codes within the sequence.

21. The system as recited in claim 9, wherein the remote control and the command  
5 receiver communicate via a network.

22. The system as recited in claim 21, wherein the network comprises the Internet.

23. A method for monitoring for the successful transmission of a command code  
10 transmitted from a remote control, the method comprising:  
receiving a transmission from the remote control;  
determining if the transmission from the remote control comprises a command  
code that is stored within a library of command codes; and  
when the transmission from the remote control is determined to not include a  
15 command code that is stored within the library of command codes, performing an action  
for the purpose of initiating a retransmission of at least those command codes in the  
sequence of command codes determined to be missing.

24. The method as recited in claim 23, wherein the action comprises generating an  
20 audible signal.

25. The method as recited in claim 22, wherein the action comprises generating an  
audible signal.

26. The method as recited in claim 22, wherein the action comprises transmitting a signal to the remote control to adapt the remote control to retransmit at least those command codes in the sequence of command codes determined to be missing

5

27. A remote control transmission monitoring system, comprising:

a remote control for transmitting a sequence of command codes; and

a command receiver for monitoring the transmission from the remote control;

wherein the command receiver is programmed such that, as each command code

10 in the sequence is received from the remote control, the command receiver confirms and acknowledges the receipt of that command code with the remote control and wherein the remote control waits for the acknowledgement before transmitting the next command code in the sequence of command codes.

15 28. The system as recited in claim 24, wherein the remote control retransmits a command code if the acknowledgement is not received within a predetermined time.

29. A method for programming a command receiver to monitor remote control transmissions, comprising:

20 receiving a transmission from the remote control to place the command receiver in a learning mode;

receiving a transmission from the remote control comprising a sequence of command codes;

storing a representation of the sequence of command codes within a memory accessible to the command receiver; and

receiving a transmission from the remote control to exit the learning mode;

whereby the representation of the sequence of command codes is available to  
5 compare against future transmissions received from the remote control to determine if the future transmission from the remote control comprises the sequence of command codes.

30. The method as recited in claim 29, further comprising causing the command receiver to retransmit any command codes determined to be missing from a transmission received  
10 from the remote control.

31. The method as recited in claim 29, wherein a label is associated with the sequence of command codes transmitted by the remote control and the method further comprises the step of storing the label within the memory.  
15

32. The method as recited in claim 31, wherein the transmission from the remote control to place the command receiver in a learning mode comprises the label.

33. A method for using a remote control to program a command receiver to monitor  
20 remote control transmissions, comprising:

transmitting from the remote control a command code to place the command receiver in a learning mode;

transmitting from the remote control a sequence of command codes where a representation of the sequence of command codes is stored within a memory accessible to the command receiver; and

transmitting from the remote control a command code to cause the command  
5 receiver to exit the learning mode;

whereby the representation of the sequence of command codes stored in the memory is available to compare against future transmissions from the remote control to determine if the future transmission from the remote control comprises the sequence of command codes.

10

34. The method as recited in claim 33, wherein a label is associated with the sequence of command codes transmitted by the remote control and the method further comprises the step of transmitting the label from the remote control to the command receiver.

15 35. The method as recited in claim 34, wherein the transmission from the remote control to place the command receiver in a learning mode comprises the label.

36. The method as recited in claim 35, wherein the label is representative of a key of the remote control which, upon activation, causes the transmission of the sequence of  
20 command codes.

37. A remote control having instructions for programming a command receiver to monitor remote control transmissions, the instructions performing steps comprising:



transmitting a command code to place the command receiver in a learning mode;  
transmitting a sequence of command codes to thereby allow a representation of  
the sequence of command codes to be stored within a memory accessible to the command  
receiver; and

5       transmitting a command code to cause the command receiver to exit the learning  
mode;

whereby the representation of the sequence of command codes stored in the  
memory is available to compare against future transmissions from the remote control to  
determine if the future transmission from the remote control comprises the sequence of  
10   command codes.

38. The remote control as recited in claim 37, wherein a label is associated with the  
transmitted sequence of command codes and the instructions further comprise the step of  
transmitting the label to the command receiver.

15

39. The remote control as recited in claim 38, wherein the transmission to place the  
command receiver in a learning mode comprises the label.

40. The remote control as recited in claim 38, wherein the label is representative of a key  
20   of the remote control which, upon activation, causes the transmission of the sequence of  
command codes.

41. The remote control as recited in claim 40, wherein the instructions further provide for user programming of the sequence of command codes and assignment of the sequence of command codes to the key.